Specifications

V1

Frame and Components

Frame	Aluminium 6061, double butted, 28",47cm
Rigid fork	Reany Bikes Custom , Alloy fork, 28"
Handlebar	Reany Bikes custom, Carbon fiber, W=630
Grips	L=R=133MM, black
Seatpost	SP-720, 3D Forged Alu, 30.9 x 350mm
Saddle	Selle Royal Essenza+
Pedals	Steady Flat non-slip pedal, with reflectors
Drivetrain	Gates drive belt CDN, 11M-122T-12CT
Chain ring	55T, for Gates drive belt CDN
Crankset	170 mm
Freewheel	22T, for Gates drive belt CDC
Bottom Bracket	Sealed BB with a torque sensor
Front hub	AL 14G*28H
Brakes	Tektro hydraulic disc brake
Tires	28"45C/47-622, 60TPI puncture proof, reflect
Tubes	28" F/V
Rims	28" , Double wall
Spokes	14G, Stainless, black(28x); 13G, Stainless, black(36X)
Front light	LED, intergrated in the handlebar, 40 LUX
Tail light	COB LED, integrated in the mudguard
Mudguards	Alu, 28" 59 mm, matte black
Bell	Reany Bikes custom
Kickstand	Reany Bikes custom

Electronics

Assist Speed	25km/h
Range	Up to 100km, depending on terraine and assist mode
Battery	Inner tube removable battery 360Wh LG with smart BMS, IPX6
Charger	2A EU standard
Motor	Mivice M070 250W 35Nm IP65
Display	LCD, custom intergrated into handlebar

Geometries

Seat Tube Length [A]	470mm
Top tube length [B]	625mm
Head tube length [C]	200mm
Head tube angle [D]	71°
Seat tube angle [E]	73°
Reach [F]	435mm
Wheelbase [G]	1140mm
Stack [H]	665mm



Chainstay length	455.5mm
Bottom bracket height	300mm
Bottom bracket Offset	60mm
Stand-over height	400mm
Overall length	1865mm
Wheel size	28"
Weight	19.1kg

The stated weight refers to the bike in its purest form(excl. pedala and accessories), reflecting our lightweight design.