

Specifications

Frame and Components

| Frame | Aluminium 6061, double butted, 28",52cm,Night Black or Sage Green, or Azure Blue |
|----------------|--|
| Rigid fork | Reany Bikes Custom , Alloy fork, 28" |
| Handlebar | Reany Bikes custom, Carbon, W=630 |
| Grips | L=R=133MM, black |
| Seatpost | HT12-D30.9*100L, Suspension seatpost, adjust travel: 100mm, |
| Saddle | Selle Royal Essenza |
| Pedals | Steady Flat non-slip pedal, with reflectors |
| Drivetrain | Gates drive belt CDN, 11M-122T-12CT |
| Chain ring | 55T, for Gates drive belt |
| Crankset | 170 mm |
| Freewheel | 22T, for Gates drive belt |
| Bottom Bracket | Sealed BB with a torque sensor |
| Front hub | AL 14G*28H |
| Brakes | Tektro hydraulic disc brake |
| Tires | 28"45C/47-622, 60TPI puncture proof, reflect |
| Tubes | 28" F/V |
| Rims | 28", Double wall |
| Spokes | 14G, Stainless, black(28x); 13G, Stainless, black(36X) |
| Front light | LED, intergrated in the handlebar, 40 LUX |
| Tail light | COB LED, integrated in the mudguard |
| Mudguards | Alu, 28" 60 mm, matte black |
| Bell | Reany Bikes custom |
| Kickstand | Reany Bikes custom |
| Luggage rack | Reay Bikes Rack, Alu, maximal 18kg |
| | |


Electronics

25km/h Assist Speed Up to 100km, depending on terraine and assist mode Range Inner tube removable battery 360Wh LG with smart BMS, IPX6 Battery 2A EU standard Charger Mivice M070 250W 35Nm IP65 Motor IPS, matrix, 2.0", custom intergrated into handlebar Display


Geometries

Seat Tube Length [A] Top tube length [B] Head tube length [C] Head tube angle [D] Seat tube angle [E] Reach [F] Wheelbase [G] Stack [H]

Bottom bracket height Bottom bracket Offset Stand-over height Chainstay length Overall length Wheel size Weight



60mm 770mm 455.5mm 1865mm 28" 19.7kg



- reanybikes.com

N1 GT